



# TIMKEN BEARINGS TRAINING INDUSTRY

3.938 Inch | 100.025 Millimeter x 5.969 Inch |  
 151.613 Millimeter x 4.25 Inch | 107.95 Millimeter  
 REXNORD KA6315F Pillow Block Bearings



Bearing No. KA6315F

KA6315F Bearing 2D drawings and 3D CAD models

|                           |   |
|---------------------------|---|
| Category                  | Pillow Block Bearings   |
| Inventory                 | 0.0   |
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 27.694  |
| EAN                       | 0793699902587   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Tapered Adapter Sleeve  |
| Housing Style             | 4 Bolt Pillow Block   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 3/4 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | 6315U   |
| Seals                     | Light Contact   |
| Housing Configuration     | 1 Piece Solid   |
| Inch - Metric             | Inch  |
| Other Features            | Double Row  |
| Long Description          | 4 Bolt Pillow Block;<br>3-15/16" Bore; 4-1/4" Base<br>to Center Height; Tapered<br>Adapter Sleeve Mount;<br>Spherical Roller Bearing;<br>Relubricatable; Cast Iron; |



# TIMKEN BEARINGS TRAINING INDUSTRY

|                               |   |
|-------------------------------|---|
|                               | Light Contact; Non-expansion                                |
| Category                      | Pillow Block  |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer URL              | <a href="http://www.rexnord.com">http://www.rexnord.com</a> |
| Manufacturer Item Number      | KA6315F   |
| Manufacturer Internal Number  | 190258  |
| Weight / LBS                  | 61  |
| d                             | 3.938 Inch   100.025 Millimeter                             |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter  |
| D                             | 5.969 Inch   151.613 Millimeter                             |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter  |
| Actual Bolt Center to Center  | 12.5 Inch   317.5Millimeter                                 |
| B                             | 4.25 Inch   107.95 Millimeter                               |
| Nominal Bolt Center to Center | 12.5 Inch   317.5 Millimeter                                |